

**EPA 600/R-00/096
October 2000**

**VOLATILIZATION RATES FROM WATER TO INDOOR AIR
PHASE II**

**National Center for Environmental Assessment–Washington Office
Office of Research and Development
U.S. Environmental Protection Agency
Washington, DC 20460**

DISCLAIMER

This document has been reviewed in accordance with U.S. Environmental Protection Agency policy and approved for publication. Mention of trade names or commercial products does not constitute endorsement or recommendation for use.

EXECUTIVE SUMMARY

Contaminated water can lead to volatilization of chemicals to residential indoor air. Previous research has focused on only one source (shower stalls) and has been limited to chemicals in which gas-phase resistance to mass transfer is of marginal significance. As a result, attempts to extrapolate chemical emissions from high-volatility chemicals to lower volatility chemicals, or to sources other than showers, have been difficult or impossible.

In this study two-phase dynamic mass balance models were developed for estimating chemical emissions from washing machines, dishwashers, and bathtubs. An existing model was adopted for showers only. The mass transfer theory and derivations of these models are further described in chapter 2 of this report. Source- and chemical-specific mass transfer coefficients, as well as air exchange (ventilation) rates were estimated based on a series of experiments. These experiments were conducted using 5 tracer chemicals (acetone, ethyl acetate, toluene, ethylbenzene, and cyclohexane) and 4 sources (showers, bathtubs, washing machines, and dishwashers). Each set of experiments led to the determination of chemical stripping efficiencies and mass transfer coefficients (overall, liquid-phase, gas-phase), and to an assessment of the importance of gas-phase resistance to mass transfer.

A set of protocols for estimating emission rates for chemicals other than those used in this study was defined for each of the four sources. Example applications are provided and illustrate the dynamic behavior of emissions and importance of chemical properties on such emissions. The experimental mass transfer coefficients, air exchange rates and protocols described in this report can be used as direct input values or to estimate reasonable input values for the reported emission models.

Stripping efficiencies ranged from 6.3% to 80% for showers, 2.6% to 69% for bathtubs, 18% to 100% for dishwashers, and 3.8% to 100% for washing machines. Acetone and cyclohexane always defined the lower and upper bounds, respectively, of these ranges.

The findings of this study lead to several conclusions. A detailed discussion of conclusions is presented in chapter 9. Some of the most significant conclusions are summarized below.

- System operating conditions can have a significant effect on chemical emissions. In particular, chemical stripping efficiencies for washing machines were observed to be highly sensitive to system operating conditions.
- Water temperature was an important variable that affected stripping efficiencies and mass transfer coefficients for all sources.

- Chemical stripping efficiencies increase as Henry's law constant increases for lower-volatility chemicals. However, with the exception of the fill-cycle of bathtubs, chemical stripping efficiencies are relatively insensitive to Henry's law constant for chemicals with constants greater than that of toluene.
- Failure to account for gas-phase resistance to mass transfer can lead to significant overestimates of chemical volatilization to indoor air. This is particularly true for lower-volatility chemicals or those sources with low values of gas- to liquid-phase mass transfer coefficients (k_g/k_l), e.g., washing machines.
- Results for shower experiments were reasonably consistent with those reported by other researchers with stripping efficiencies ranging from 60% to 80% for chemicals with Henry's law constant equal or greater than that of toluene.
- Gas-phase concentrations were homogeneous throughout the shower stall demonstrating that the frequent assumption of a well-mixed system is reasonably accurate.
- Dishwashers were determined to be very effective at removing chemicals from water to air, with low but continuous emissions during operation and significant storage within the dishwasher headspace. The most significant release of chemicals to indoor air would occur if the dishwasher door is opened immediately after use.
- Washing machines during the rinse cycle with hot water and low clothes loading resulted in stripping efficiencies that approached 100% for chemicals with Henry's law constant greater than toluene.
- Bathtubs may be more significant than showers with respect to human exposure to chemicals dissolved in water because of longer exposure times.

CONTENTS

List of Tables	x
List of Figures	xiii
Nomenclature and Abbreviations	xv
Preface	xviii
Authors, Contributors, and Reviewers	xix
Acknowledgments	xx
1. Introduction	1-1
1.1. Problem Statement	1-1
1.2. Research Objectives	1-2
1.3. Scope of Research	1-2
1.4. Organization of Research Report	1-2
2. Model Development	2-1
2.1. Mass Transfer Theory	2-1
2.1.1. Chemical Stripping Efficiency	2-1
2.1.2. Mass Transfer Coefficients	2-2
2.2. Ideal Reactor Models	2-9
2.2.1. Plug Flow Reactor Model	2-9
2.2.2. Continuous-Flow Stirred-Tank Reactor Model	2-10
2.2.3. Batch Reactor Model	2-11
2.3. Source-Specific Mass Balance Models	2-12
2.3.1. Dishwasher Models	2-12
2.3.2. Washing Machine Models	2-16
2.3.2.1. Washing Machine Fill Cycle	2-16
2.3.2.2. Washing Machine Wash/Rinse Cycles	2-18
2.3.3. Shower Models	2-18
2.3.4. Bathtub Models	2-21
2.3.4.1. Bathtub Flow-Through Model	2-21
2.3.4.2. Bathtub Fill Model	2-21
2.3.4.3. Bathtub Surface Volatilization Model	2-21
2.4. Chemical Emission Models	2-22

CONTENTS (continued)

3. General Methodology	3-1
3.1. Source Chamber	3-1
3.2. Chemical Tracers	3-2
3.2.1. Physicochemical Properties	3-2
3.2.2. Chemical Tracer Addition	3-3
3.3. Chemical Sampling	3-4
3.3.1. Liquid-Phase Sampling	3-4
3.3.2. Gas-Phase Sampling	3-5
3.4. Sample Analyses	3-6
3.4.1. Liquid Sample Analysis	3-6
3.4.2. Liquid Standards	3-7
3.4.3. Gas Sample Analysis	3-9
3.4.4. Gas Standards	3-9
3.5. Quality Assurance Measures	3-11
3.5.1. Duplicate Samples	3-11
3.5.2. Replicate Experiments	3-12
3.5.3. Experimental Blanks	3-13
3.5.4. Method Detection Limit	3-13
3.6. Data Analysis	3-14
3.6.1. Chemical Stripping Efficiencies	3-15
3.6.2. Overall Mass Transfer Coefficients (K_LA)	3-15
3.6.3. Ratio of Gas-to-Liquid Phase Mass Transfer Coefficients	3-17
3.6.4. Liquid- and Gas-Phase Mass Transfer Coefficients	3-18
3.7. Factorial Analysis	3-18
3.8. Mass Closure Assessment	3-18
4. Shower Stall Experiments	4-1
4.1. Experimental System	4-1
4.2. Experimental Design	4-3
4.3. Source-Specific Methodology	4-4
4.3.1. Sample Schedule	4-4
4.3.2. Ventilation Rate	4-5
4.3.3. Parameter Estimation	4-5
4.4. Shower Results	4-5
4.4.1. Chemical Stripping Efficiencies	4-5

CONTENTS (continued)

4.4.2.	K_LA Values	4-17
4.4.3.	Liquid- and Gas-Phase Mass Transfer Coefficients	4-26
4.4.4.	Mass Closure	4-30
5.	Dishwasher Experiments	5-1
5.1.	Experimental System	5-1
5.2.	Experimental Design	5-2
5.3.	Source-Specific Methodology	5-3
5.3.1.	Sample Schedule	5-4
5.3.2.	Ventilation Rate	5-4
5.3.3.	Parameter Estimation	5-4
5.4.	Dishwasher Results	5-7
5.4.1.	Ventilation Rates	5-7
5.4.2.	Chemical Stripping Efficiencies	5-8
5.4.3.	K_LA Values	5-13
5.4.4.	Liquid- and Gas-Phase Mass Transfer Coefficients	5-20
5.4.5.	Mass Closure	5-21
6.	Washing Machine Experiments	6-1
6.1.	Fill Cycle Experiments	6-1
6.1.1.	Experimental System	6-1
6.1.2.	Experimental Design	6-3
6.1.3.	Source-Specific Methodology	6-3
6.1.3.1.	Sample Schedule	6-4
6.1.3.2.	Ventilation Rates	6-5
6.1.3.3.	Parameter Estimation	6-6
6.1.4.	Fill Cycle Results	6-7
6.1.4.1.	Ventilation Rates	6-8
6.1.4.2.	Chemical Stripping Efficiencies	6-9
6.1.4.3.	K_LA Values	6-11
6.1.4.4.	Liquid- and Gas-Phase Mass Transfer Coefficients	6-12
6.1.4.5.	Mass Closure	6-14
6.2.	Wash/Rinse Cycle Experiments	6-14
6.2.1.	Experimental System	6-14
6.2.2.	Experimental Design	6-15

CONTENTS (continued)

6.2.3.	Source-Specific Methodology	6-15
6.2.3.1.	Sample Schedule	6-16
6.2.3.2.	Ventilation Rates	6-17
6.2.3.3.	Parameter Estimation	6-17
6.2.4.	Wash/Rinse Cycle Results	6-18
6.2.4.1.	Ventilation Rates	6-19
6.2.4.2.	Chemical Stripping Efficiencies	6-23
6.2.4.3.	K_LA Values	6-38
6.2.4.4.	Liquid- and Gas-Phase Mass Transfer Coefficients	6-51
6.2.4.5.	Mass Closure	6-54
7.	Bathtub Experiments	7-1
7.1.	Bathtub Flow-Through Experiments	7-1
7.1.1.	Experimental System	7-1
7.1.2.	Experimental Design	7-1
7.1.3.	Source-Specific Methodology	7-1
7.1.3.1.	Sample Schedule	7-1
7.1.3.2.	Ventilation Rate	7-2
7.1.3.3.	Parameter Estimation	7-2
7.1.4.	Bathtub Flow-Through Results	7-3
7.1.4.1.	Chemical Stripping Efficiencies	7-3
7.1.4.2.	K_LA Values	7-5
7.1.4.3.	Liquid- and Gas-Phase Mass Transfer Coefficients	7-7
7.1.4.4.	Mass Closure	7-8
7.2.	Bathtub Fill Experiments	7-9
7.2.1.	Experimental System	7-9
7.2.2.	Experimental Design	7-9
7.2.3.	Source-Specific Methodology	7-9
7.2.3.1.	Sample Schedule	7-9
7.2.3.2.	Ventilation Rates	7-11
7.2.3.3.	Parameter Estimation	7-11
7.2.4.	Bathtub Fill Results	7-11
7.2.4.1.	Chemical Stripping Efficiencies	7-11
7.2.4.2.	Values	7-13
7.2.4.3.	Liquid- and Gas-Phase Mass Transfer Coefficients	7-13

7.2.4.4.	Mass Closure	7-13
7.3.	Surface Volatilization Experiments	7-14
7.3.1.	Experimental System	7-14
7.3.2.	Experimental Design	7-15
7.3.3.	Source-Specific Methodology	7-15
7.3.3.1.	Sample Schedule	7-15
7.3.3.2.	Ventilation Rates	7-15
7.3.3.3.	Parameter Estimation	7-15
7.3.4.	Bathtub Surface Volatilization Results	7-16
7.3.4.1.	Chemical Stripping Efficiencies	7-17
7.3.4.2.	K_LA Values	7-18
7.3.4.3.	Liquid- and Gas-Phase Mass Transfer Coefficients	7-19
7.3.4.4.	Mass Closure	7-19
8.	Model Applications	8-1
8.1.	Shower Model Application	8-1
8.2.	Dishwasher Model Application	8-7
8.3.	Washing Machine Model Application	8-13
8.4.	Bathtub Model Application	8-19
9.	Summary and Conclusions	9-1
9.1.	Summary	9-1
9.2.	Conclusions: General	9-3
9.3.	Conclusions: Showers	9-4
9.4.	Conclusions: Dishwashers	9-5
9.5.	Conclusions: Washing Machines	9-6
9.6.	Conclusions: Bathtubs	9-7
9.7.	Recommendations for Future Research	9-8
10.	References	10-1
	Appendix: Chemical Volatilization Database	A-1

LIST OF TABLES

3-1	Summary of physicochemical properties for selected chemical tracers	3-2
3-2	Duplicate sample results	3-11

LIST OF TABLES (continued)

3-3	Replicate sample results	3-12
3-4	Replicate sample results excluding replicate experiments associated with filling	3-13
3-5	Method detection limits (MDLs) for liquid and gas samples	3-14
4-1	Shower experiment operating conditions	4-2
4-2	Acetone stripping efficiencies for experimental shower	4-7
4-3	Ethyl acetate stripping efficiencies for experimental shower	4-7
4-4	Toluene stripping efficiencies for experimental shower	4-9
4-5	Ethylbenzene stripping efficiencies for experimental shower	4-9
4-6	Cyclohexane stripping efficiencies for experimental shower	4-11
4-7	Acetone K_LA values for experimental shower	4-20
4-8	Ethyl acetate K_LA values for experimental shower	4-20
4-9	Toluene K_LA values for experimental shower	4-21
4-10	Ethylbenzene K_LA values for experimental shower	4-21
4-11	Cyclohexane K_LA values for experimental shower	4-22
4-12	Liquid- and gas-phase mass transfer coefficients for shower experiments	4-30
5-1	Dishwasher experimental operating conditions	5-7
5-2	Dishwasher ventilation rate experimental results	5-9
5-3	Chemical stripping efficiencies (O) for experimental dishwasher	5-10
5-4	Acetone K_LA values for dishwasher experiments	5-14
5-5	Toluene K_LA values for dishwasher experiments	5-14
5-6	Ethylbenzene K_LA values for dishwasher experiments	5-15
5-7	Cyclohexane K_LA values for dishwasher experiments	5-15
6-1	Washing machine fill cycle experimental conditions	6-8
6-2	Washing machine fill cycle ventilation rates	6-9
6-3	Chemical stripping efficiencies (O) for washing machine fill cycles	6-10
6-4	Values of K_LA for washing machine fill cycles	6-12
6-5	Liquid- and gas-phase mass transfer coefficients for washing machine fill cycle experiments	6-13
6-6	Washing machine wash/rinse cycle experimental operating conditions	6-19
6-7	Ventilation rate experimental results	6-21
6-8	Acetone stripping efficiencies for washing machine wash/rinse cycle—Factorial #1	6-23
6-9	Acetone stripping efficiencies for washing machine wash/rinse cycle—Factorial #2	6-25
6-10	Ethyl acetate stripping efficiencies for washing machine wash/rinse cycle—Factorial #2	6-25
6-11	Toluene stripping efficiencies for washing machine wash/rinse cycle—Factorial #1	6-27

LIST OF TABLES (continued)

6-12	Toluene stripping efficiencies for washing machine wash/rinse cycle—Factorial #2 . . .	6-27
6-13	Ethylbenzene stripping efficiencies for washing machine wash/rinse cycle— Factorial #1	6-29
6-14	Ethylbenzene stripping efficiencies for washing machine wash/rinse cycle— Factorial #2	6-29
6-15	Cyclohexane stripping efficiencies for washing machine wash/rinse cycle— Factorial #1	6-31
6-16	Cyclohexane stripping efficiencies for washing machine wash/rinse cycle— Factorial #2	6-31
6-17	Acetone K_LA values for washing machine wash/rinse cycle—Factorial #1	6-40
6-18	Acetone K_LA values for washing machine wash/rinse cycle—Factorial #2	6-40
6-19	Ethyl acetate K_LA values for washing machine wash/rinse cycle—Factorial #2	6-41
6-20	Toluene K_LA values for washing machine wash/rinse cycle—Factorial #1	6-41
6-21	Toluene K_LA values for washing machine wash/rinse cycle—Factorial #2	6-42
6-22	Ethylbenzene K_LA values for washing machine wash/rinse cycle—Factorial #1	6-42
6-23	Ethylbenzene K_LA values for washing machine wash/rinse cycle—Factorial #2	6-43
6-24	Cyclohexane K_LA values for washing machine wash/rinse cycle—Factorial #1	6-43
6-25	Cyclohexane K_LA values for washing machine wash/rinse cycle—Factorial #2	6-45
6-26	Liquid- and gas-phase mass transfer coefficients for washing machine wash/rinse cycle experiments—Factorial #1	6-55
6-27	Liquid- and gas-phase mass transfer coefficients for washing machine wash/rinse cycle experiments—Factorial #2	6-56
7-1	Bathtub flow-through operating conditions	7-3
7-2	Chemical stripping efficiencies (O) for experimental bathtub flow-through experiments	7-4
7-3	Values of K_LA for bathtub flow-through experiments	7-5
7-4	Liquid- and gas-phase mass transfer coefficients for bathtub flow-through experiments.	7-7
7-5	Bathtub (fill) operating conditions	7-12
7-6	Chemical stripping efficiencies (O) for bathtub (fill) experiments	7-12
7-7	Values of K_LA for bathtub (fill) experiments	7-13
7-8	Liquid- and gas-phase mass transfer coefficients for bathtub (fill) experiments	7-14
7-9	Bathtub surface volatilization operating conditions	7-17
7-10	Chemical stripping efficiencies for bathtub surface volatilization experiments	7-18
7-11	Values of K_LA for bathtub surface volatilization experiments	7-18

LIST OF TABLES (continued)

7-12 Liquid- and gas-phase mass transfer coefficients for bathtub surface volatilization
experiments 7-21

8-1 Comparison of the three chemicals used in model applications 8-2

9-1 Summary of experimental stripping efficiencies and k_g/k_l 9-2

LIST OF FIGURES (continued)

LIST OF FIGURES

2-1	Plug flow reactor	2-10
2-2	Continuous-flow stirred-tank reactor	2-11
2-3	Batch reactor	2-11
2-4	Dishwasher model	2-13
2-5	Washing machine fill cycle model	2-17
2-6	Washing machine wash/rinse cycle model	2-18
2-7	Shower model	2-19
2-8	Bathtub flow-through model	2-22
2-9	Bathtub fill model	2-22
2-10	Bathtub surface volatilization model	2-23
3-1	Gas sampling experimental set up	3-6
3-2	Liquid-phase sample chromatogram	3-7
3-3	Liquid-phase calibration curve for ethylbenzene	3-8
3-4	Gas sample chromatogram	3-10
3-5	Gas-phase calibration curve for acetone	3-10
3-6	Matrix format used to determine k_g/k_l	3-19
4-1	Shower experimental system	4-2
4-2	Shower factorial experimental design	4-3
4-3	Relationship between Henry's law constant and average stripping efficiency	4-18
4-4	Acetone experimental data for Experiment 7	4-23
4-5	Ethyl acetate experimental data for Experiment 7	4-25
4-6	Toluene experimental data for Experiment 7	4-26
4-7	Ethylbenzene experimental data for Experiment 7	4-27
4-8	Cyclohexane experimental data for Experiment 7	4-28
4-9	Resistances to mass transfer for each chemical in Experiment 7	4-32
5-1	Dishwasher experimental system	5-2
5-2	Factorial experimental design for dishwasher experiments	5-3
5-3	Isobutylene decay due to ventilation for Experiment 18	5-9
5-4	Comparison of measured C_g/C_l predicted Henry's law constant for acetone	5-17
5-5	Toluene concentrations for Experiment 8	5-18
5-6	Amplification of Figure 30 to illustrate approach to equilibrium conditions for toluene	5-19

LIST OF FIGURES (continued)

5-7	Ethylbenzene concentrations for Experiment 8	5-20
5-8	Cyclohexane concentrations for Experiment 8	5-20
6-1	Washing machine fill cycle experimental system	6-2
6-2	Isobutylene decay due to ventilation for Experiment 13	6-9
6-3	Wash/rinse cycle experimental system	6-15
6-4	Wash/rinse cycle factorial experimental design	6-16
6-5	Isobutylene decay due to ventilation for Experiment 8	6-23
6-6	Acetone concentrations for Experiment 6	6-46
6-7	Amplification of Figure 6-6 for acetone gas-phase data	6-48
6-8	Toluene concentrations for Experiment 6	6-49
6-9	Magnification of Figure 6-8 to illustrate toluene's gas-phase concentration over time	6-49
6-10	Ethylbenzene concentrations for Experiment 6	6-51
6-11	Cyclohexane concentrations for Experiment 6	6-51
6-12	Liquid- and gas-phase resistances to mass transfer for Experiment 6	6-44
7-1	Bathtub flow-through experimental system	7-2
7-2	Toluene experimental data for Experiment 4 replicate	7-6
7-3	Resistances to mass transfer for each chemical in Experiment 2	7-8
7-4	Bathtub fill experimental system	7-10
7-5	Toluene experimental data for Experiment 4 replicate	7-19
8-1	Mass emission rates for three chemicals for example shower event	8-2
8-2	Mass emission rates for three chemicals for example dishwasher event	8-11
8-3	Amplification of Figure 52 to show methyl ethyl ketone mass emission rate	8-12
8-4	Mass emission rates for three chemicals for example washing machine event	8-18
8-5	Mass emission rates for three chemicals for example bathtub event	8-20

NOMENCLATURE AND ABBREVIATIONS¹

A	interfacial surface area between water and adjacent air (L^2)
ACH	air changes per hour
ΔA	differential ¹ area (L^2)
C	chemical concentration (M/L^3)
C_{expt}	experimentally measured liquid- and gas-phase concentrations (M/L^3)
C_g	chemical concentration in air adjacent to water (M/L^3)
$C_{g,\text{in}}$	inlet concentration of contaminant in air (M/L^3)
$C_{g,0}$	initial chemical concentration in gas volume (M/L^3)
$C_{g,t}$	chemical concentration in air at any time t (M/L^3)
C_{in}	inlet chemical concentration (M/L^3)
C_l	chemical concentration in water (M/L^3)
$C_{l,\text{end}}$	final chemical concentration in water (M/L^3)
$C_{l,\text{in}}$	inlet chemical concentration in water (M/L^3)
$C_{l,\text{out}}$	outlet concentration of contaminant in water (M/L^3)
$C_{l,0}$	initial chemical concentration in water (M/L^3)
C_m	mathematically predicted liquid- and gas-phase concentrations (M/L^3)
CFSTR	continuous flow stirred tank reactor
cosh	hyperbolic cosine
coth	hyperbolic cotangent
D_g	molecular diffusion coefficient for a chemical in air (L^2/T)
D_{gi}	molecular diffusion coefficient for chemical i in air (L^2/T)
D_{gj}	molecular diffusion coefficient for chemical j in air (L^2/T)
D_l	molecular diffusion coefficient for a contaminant in water (L^2/T)
D_{li}	molecular diffusion coefficient for chemical i in water (L^2/T)
D_{lj}	molecular diffusion coefficient for chemical j in water (L^2/T)
DBCM	dibromochloromethane
DBCP	1,2-dibromo-3-chloropropane
E_{chem}	chemical mass emission rate (M/T)
FID	flame ionization detector
GC	gas chromatography

¹ Note: Terms in parentheses denote units; M corresponds to mass; L corresponds to length; T corresponds to time; ($^{\circ}$) corresponds to temperature; dimensionless values are denoted as (-).

NOMENCLATURE AND ABBREVIATIONS (continued)

H_c	Henry's law constant ($L^3_{\text{gas}}/L^3_{\text{liq}}$)
$H_{c,i}$	Henry's law constant for chemical i ($L^3_{\text{gas}}/L^3_{\text{liq}}$)
$H_{c,j}$	Henry's law constant for chemical j ($L^3_{\text{gas}}/L^3_{\text{liq}}$)
$H_{c,T}$	Henry's law constant at experimental temperature ($L^3_{\text{gas}}/L^3_{\text{liq}}$)
ID	inside diameter (L)
k_g	gas-phase mass transfer coefficient (L/T)
k_{gi}	gas-phase mass transfer coefficient for chemical i (L/T)
k_{gj}	gas-phase mass transfer coefficient for chemical j (L/T)
K_L	overall mass transfer coefficient for contaminant of interest (L/T)
k_l	liquid-phase mass transfer coefficient (L/T)
K_{Li}	overall mass transfer coefficient for chemical i (L/T)
k_{li}	liquid-phase mass transfer coefficient for chemical i (L/T)
K_{Lj}	overall mass transfer coefficient for chemical j (L/T)
k_{lj}	liquid-phase mass transfer coefficient for chemical j (L/T)
m_c	degree of mass closure (-)
MDL	method detection limit
MEK	methyl ethyl ketone
n_1	power constant for ratio of liquid-phase diffusion coefficients (-)
n_2	power constant for ratio of gas-phase diffusion coefficients (-)
OD	outside diameter (L)
P	perimeter (L)
pFR	plug flow reactor
Pv	vapor pressure (L Hg)
Q	volumetric flowrate (L^3/T)
Q_g	gas flowrate (L^3/T)
Q_{in}	inlet volumetric flowrate (L^3/T)
Q_l	liquid flowrate (L^3/T)
Q_{out}	outlet volumetric flowrate (L^3/T)
r_A	area reaction rate ($M/L^2 \cdot T$)
r_g	rate of surface renewal for the gas side of the interface (1/T)
r_l	rate of surface renewal for the liquid side of the interface (1/T)
r_V	volume reaction rate ($M/L^3 \cdot T$)
sinh	hyperbolic sine
s_r	standard deviation of replicate analyses

NOMENCLATURE AND ABBREVIATIONS (continued)

t	time (T)
T	temperature ($^{\circ}\text{C}$)
T_b	boiling point ($^{\circ}\text{C}$)
TCE	trichloroethene
TKE	total kinetic energy
V	volume (L^3)
ΔV	differential volume (L^3)
V_g	local volume of air (L^3)
V_l	local volume of water (L^3)
z	direction of flow
δ_g	thickness of a hypothetical gas film adjacent to the interface and through which contaminant transport is solely by molecular diffusion (L)
δ_l	thickness of a hypothetical liquid film adjacent to the interface and through which contaminant transport is solely by molecular diffusion (L)
η	chemical stripping efficiency (-)
ρ	density (M/L^3)
Ψ_g	gas-phase mass transfer relational coefficient (-)
Ψ_l	liquid-phase mass transfer relational coefficient (-)
Ψ_m	overall mass transfer relational coefficient (-)

PREFACE

This report was prepared under the direction of the National Center for Environmental Assessment (NCEA) of EPA's Office of Research and Development (ORD). The purpose of this report is to provide a methodology for estimating chemical emissions from washing machines, dishwashers, showers, and bathtubs. The methodology presented in this report was derived from volatilization experiments conducted by The University of Texas at Austin under a Cooperative Agreement with NCEA. Results of these experiments are included in the report.

AUTHORS, CONTRIBUTORS, AND REVIEWERS

This report was prepared under Cooperative Agreement #CR 824228-01 between The University of Texas at Austin and the National Center for Environmental Assessment (NCEA), Office of Research and Development. It covers a period from June 1, 1995 to August 31, 1997, and work was completed as of August 31, 1997. Jackie Moya was responsible for the overall coordination, direction, and technical assistance.

AUTHORS

Cynthia Howard-Reed
formerly Graduate Research Assistant with The University of Texas at Austin
presently with the Indoor Air Quality Group at the National Institute of Standards and
Technology (NIST)

Richard L. Corsi
Principal Investigator
Environmental and Water Resources Engineering Program
The University of Texas at Austin

REVIEWERS

The following individuals have reviewed this report and provided valuable comments:

Environmental Protection Agency Reviewers

Jacqueline Moya
Nancy Chiu
Lance Wallace

External Reviewers

John Little
Associate Professor
Civil and Environmental Engineering
Virginia Tech
Blacksburg, VA

Nicholas J. Giardino
Toxicologist
Brooks AFB, Texas

ACKNOWLEDGMENTS

The authors wish to thank EPA Project Officer Jacqueline Moya for her general guidance and enthusiasm regarding this project. The authors also wish to acknowledge Albert Chung, Jennifer Pettibon, Javier Ramirez, Tony Smith, and Ross Strader, undergraduate students at The University of Texas at Austin, for their assistance during experiments.