Term
abiotic
Definition: Not biotic; not formed by biologic processes.
absolute viscosity
Definition: A measure of a fluid's resistance to tangential or shear stress. Also referred to as dynamic viscosity; see also viscosity. Units are usually given in centipoise.
absorption
Definition: The penetration of stame, ions or melecular into the bulk mass of a substance
Definition: The penetration of atoms, ions or molecules into the bulk mass of a substance.
actinomycetes
Definition: Any of numerous, generally filamentous, and often pathogenic, microorganisms resembling both bacteria and fungi.
adsorption
Definition: The retention of atoms, ions or molecules onto the surface of another substance.
advection
Definition: The process of transfer of fluids (vapors or liquid) through a geologic formation in response to a pressure gradient that may
be caused by changes in barometric pressure, water table levels, wind fluctuations, or infiltration.
aeration

Term
Definition: The process of bringing air into contact with a liquid (typically water), usually by bubbling air through the liquid, spraying
the liquid into the air, allowing the liquid to cascade down a waterfall, or by mechanical agitation. Aeration serves to (1) strip dissolved
gases from solution, and/or (2) oxygenate the liquid. The rate at which a gas transfers into solution can be described by Fick's first
law.
aerobic
Definition: Able to live, grow, or take place only when free oxygen is present.
afterburner
Definition: An off-gas posttreatment unit for control of organic compounds by thermal oxidation. A typical afterburner is a refractory-
lined shell providing enough residence time at sufficiently high temperature to destroy organic compounds in the off-gas stream.
aggregate
Definition: Coarse mineral material (e.g., sand, gravel) that is mixed with either cement to form concrete or tarry hydrocarbons to form
asphalt.
air sparging
Definition: An environmental cleanup method that bubbles air through contaminated groundwater to transfer volatile contaminants
from the groundwater to the soil gas, which then conveys the contaminants to the surface, where the contaminants may be captured
or allowed to disperse in the atmosphere. Air sparging systems are often used together with soil vapor extraction systems.
Acronym: AS

Term
algae
Definition: Chiefly aquatic, eucaryotic one-celled or multicellular plants without true stems, roots and leaves, that are typically autotrophic, photosynthetic, and contain chlorophyll. Algae are not typically found in groundwater.
aliphatic
Definition: Of or pertaining to a broad category of carbon compounds distinguished by a straight, or branched, open chain arrangement of the constituent carbon atoms. The carbon-carbon bonds may be either saturated or unsaturated. Alkanes, alkenes, and alkynes are aliphatic hydrocarbons.
alkanes
Definition: The homologous group of linear saturated aliphatic hydrocarbons having the general formula Cn2Hn+2. Alkanes can be straight chains, branched chains, or ring structures. Also referred to as paraffins. alkenes
Definition: The group of unsaturated hydrocarbons having the general formula CnH2n and characterized by being highly chemically reactive. Also referred to as olefins.
alkynes
Definition: The group of unsaturated hydrocarbons with a triple carbon-carbon bond having the general formula CnH2n-2. ambient

Term
Definition: Surrounding; the surrounding environment and conditions.
American Society of Testing and Materials
Acronym: ASTM
anaerobic
Definition: Able to live, grow, or take place where free oxygen is not present.
analog
Definition: In chemistry, a structural derivative of a parent compound.
anisotropic
Definition: The condition in which hydraulic properties of an aquifer are not equal when measured in all directions.
anoxic
Definition: Total deprivation of oxygen.
aqueous solubility
Definition: The extent to which a compound will dissolve in water. The log of solubility is generally inversely related to molecular weight.

Term
aquifer
Definition: A geologic formation capable of transmitting significant quantities of groundwater under normal hydraulic gradients.
aquitard
Definition: A geologic formation that may contain groundwater but is not capable of transmitting significant quantities of groundwater
under normal hydraulic gradients. In some situations aquitards may function as confining beds.
aromatic
Definition: Of or relating to organic compounds that resemble benzene in chemical behavior. These compounds are unsaturated and
characterized by containing at least one 6-carbon benzene ring.
asymptote
Definition: A line that is considered to be the limit to a curve. As the curve approaches the asymptote, the distance separating the
curve and the asymptote continues to decrease, but the curve never actually intersects the asymptote.
atmosphere (pressure)
Acronym: atm
attenuation

Term
Definition: The reduction or lessening in amount (e.g., a reduction in the amount of contaminants in a plume as it migrates away from the source).
Atterberg limits
Definition: The moisture contents which define a soil's liquid limit, plastic limit, and sticky limit.
auger
Definition: A tool for drilling/boring into unconsolidated earth materials (soil) consisting of a spiral blade wound around a central stem
or shaft that is commonly hollow (hollow-stem auger). Augers commonly are available in flights (sections) that are connected together
to advance the depth of the borehole.
autoignition temperature
Definition: The temperature at which a substance will spontaneously ignite. Autoignition temperature is an indicator of thermal stability
for petroleum hydrocarbons.
autotrophic
Definition: Designating or typical of organisms that derive carbon for the manufacture of cell mass from inorganic carbon (carbon
dioxide).
back reamer
Definition: A device pushed or pulled into the borehole to enlarge the diameter of the borehole.

Term
bacteria
Definition: Unicellular microorganisms that exist either as free-living organisms or as parasites and have a broad range of
biochemical, and often pathogenic, properties. Bacteria can be grouped by form into five general categories: cocci (spherical), bacilli
(rod-shaped), vibrio (curved rod-shaped), spirilla (spiral), and filamentous (thread-like).
baghouse
Definition: A dust-collection chamber containing numerous permeable fabric filters through which the exhaust gases pass. Finer
particulates entrained in the exhaust gas stream are collected in the filters for subsequent treatment/disposal.
ball valve
Definition: A valve regulated by the position of a free-floating ball that moves in response to fluid or mechanical pressure.
bent sub
Definition: See definition for bent sub.
bent subassembly
Definition: A device that can be used in horizontal directional drilling to change the drilling path. It attached as part of the drill string,
between the drillhead and the drill pipe. Also known as a bent sub.
Bentonite

Term
Definition: A colloidal clay, largely made up of the mineral sodium montmorillonite, a hydrated aluminum silicate. Because of its expansive property, bentonite is commonly used to provide a tight seal around a well casing.
Benzene, Toluene, Ethylbenzene, Xylenes
Acronym: BTEX
berm
Definition: A sloped wall or embankment (typically constructed of earth, hay bales, or timber framing) used to prevent inflow or outflow
of material into/from an area.
bioassay
Definition: A method used to determine the toxicity of specific chemical contaminants. A number of individuals of a sensitive species
are placed in water containing specific concentrations of the contaminant for a specified period of time.
bioaugmentation
Definition: The introduction of cultured microorganisms into the subsurface environment for the purpose of enhancing bioremediation
of organic contaminants. Generally the microorganisms are selected for their ability to degrade the organic compounds present at the
remediation site. The culture can be either an isolated genus or a mix of more than one genera. Nutrients are usually also blended
with the aqueous solution containing the microbes to serve as a carrier and dispersant. The liquid is introduced into the subsurface
under natural conditions (gravity fed) or injected under pressure.
bioavailability

Term
Definition: The availability of a compound for biodegradation, influenced by the compound's location relative to microorganisms and
its ability to dissolve in water.
biocide
Definition: A substance capable of destroying (killing) living organisms.
biodegradability
Definition: The relative ease with which petroleum hydrocarbons will degrade as the result of biological metabolism. Although virtually
all petroleum hydrocarbons are biodegradable, biodegradability is highly variable and dependent somewhat on the type of
hydrocarbon. In general, biodegradability increases with increasing solubility; solubility is inversely proportional to molecular weight.
biodegradation
Definition: A process by which microbial organisms transform or alter (through metabolic or enzymatic action) the structure of
chemicals introduced into the environment.
biodegradation potential
biomass
Definition: The amount of living matter in a given area or volume.
bioremediation

Term
Definition: An environmental cleanup method that uses microbes to clean up contaminated soil and groundwater.
biostimulation
Definition: Providing nutrients needed by microorganisms to enhance the conditions for bioremediation.
blind well
Definition: A well drilled using horizontal directional drilling with only an entry hole, through which the well materials are pushed into
the borehole.
boiling point
Definition: The temperature at which a component's vapor pressure equals atmospheric pressure. Boiling point is a relative indicator
of volatility and generally increases with increasing molecular weight.
British Thermal Unit
A or on ym: Ptu
Acronym: Btu
bubble radius
Definition: The maximum radial distance away from a biosparging well where the effects of sparging are observable. Analogous to
radius of influence of an air sparging well.

Term
bulk density
Definition: The amount of mass of a soil per unit volume of soil; where mass is measured after all water has been extracted and total volume includes the volume of the soil itself and the volume of air space (voids) between the soil grains.
butterfly valve
Definition: A shut-off valve usually found in larger pipe sizes (4 inches or greater). This type of valve can be used for non-critical flow control.
capillary fringe
Definition: The zone of a porous medium above the water table within which the porous medium is saturated by water under pressure that is less than atmospheric pressure.
capillary suction
Definition: The process whereby water rises above the water table into the void spaces of a soil due to tension between the water and soil particles.
carrier casing
Definition: Steel pipe that can be installed in the borehole to prevent borehole collapse or to prevent the well materials from digging into the side of the curved section of the borehole.
catalytic oxidizer

Term
Definition: An off-gas posttreatment unit for control of organic compounds. Gas enters the unit and passes over a support material coated with a catalyst (commonly a noble metal such as platinum or rhodium) that promotes oxidation of the organics. Catalytic
oxidizers can also be very effective in controlling odors. High moisture content and the presence of chlorine or sulfur compounds can
adversely affect the performance of the catalytic oxidizer.
centimeters per second
Acronym: cm/sec
chemotrophs
Definition: Organisms that obtain energy from oxidation or reduction of inorganic or organic matter.
coefficient of permeability
Definition: See definition for hydraulic conductivity.
colony forming units
Acronym: CFU
cometabolism
Definition: The simultaneous metabolism of two compounds, in which the degradation of the second compound(the secondary
substrate) depends on the presence of the first compound (the primary substrate). For example, in the process of degrading

Term
methane, some bacteria can degrade hazardous chlorinated solvents that they would otherwise be unable to attack.
complexation
Definition: A reaction in which a metal ion and one or more anionic ligands chemically bond. Complexes often prevent the
precipitation of metals.
condensate
Definition: The liquid that separates from a vapor during condensation.
conductivity
Definition: A coefficient of proportionality describing the rate at which a fluid (e.g., water or gas) can move through a permeable
medium. Conductivity is a function of both the intrinsic permeability of the porous medium and the kinematic viscosity of the fluid
which flows through it.
cone of depression
Definition 1: The area around a discharging well where the hydraulic head (potentiometric surface) in the aquifer has been lowered by
pumping. In an unconfined aquifer, the cone of depression is a cone-shaped depression in the water table where the media has
actually been dewatered. Definition 2: A depression in the groundwater table (or potentiometric surface) that has the shape of an
inverted cone and develops around a vertical discharge well.
cone penetrometer testing

Term
Acronym: CPT
confined aquifer
Definition: A fully saturated aquifer overlain by a confining layer. The potentiometric surface (hydraulic head) of the water in a
confined aquifer is at an elevation that is equal to or higher than the base of the overlying confining layer. Discharging wells in a
confined aquifer lower the potentiometric surface which forms a cone of depression, but the saturated media is not dewatered.
confining layer
Definition: A geologic formation characterized by low permeability that inhibits the flow of water.
conservative
Definition: In the case of a contaminant, one that does not degrade and the movement of which is not retarded; is unreactive. (b) in
the case of an assumption, one that leads to a worst-case scenario, one that is most protective of human health and the environment.
constituent
Definition: An essential part or component of a system or group (e.g., an ingredient of a chemical mixture). For instance, benzene is
one constituent of gasoline.
contaminant of concern
Acronym: COC

Term
continuous well
Preferred Term: surface-to-surface well
corrective action plan
Acronym: CAP
cyclone
Definition: A type of separator for removal of larger particles from an exhaust gas stream. Gas laden with particulates enters the cyclone and is directed to flow in a spiral causing the entrained particulates to fall out and collect at the bottom. The gas exits near the top of the cyclone. Darcy's Law
Dalcy's Law
Definition: An empirical relationship between hydraulic gradient and the viscous flow of water in the saturated zone of a porous medium under conditions of laminar flow. The flux of vapors through the voids of the vadose zone can be related to a pressure gradient through the air permeability by Darcy's Law.
degradation potential
Definition: The degree to which a substance is likely to be reduced to a simpler form by bacterial activity. denitrification

Term
Definition: Bacterial reduction of nitrite to gaseous nitrogen under anaerobic conditions.
dense non-aqueous phase liquid
Acronym: DNAPL
density
Definition: The amount of mass per unit volume.
diffusion
Definition: The process by which molecules in a single phase equilibrate to a zero concentration gradient by random molecular
motion (Brownian motion). The flux of molecules is from regions of high concentration to low concentration and is governed by Fick's
Second Law.
direct push technology
Acronym: DPT
dispersion
Definition: The process by which a substance or chemical spreads and dilutes in flowing groundwater or soil gas.
dissolution

Term
Definition: Dissolving of a substance in a liquid solvent (e.g., water).
dissolved oxygen
Acronym: DO
double ended well
Preferred Term: surface-to-surface well
downgradient
Definition: In the direction of decreasing static head (potential).
drawdown
Definition: Lowering the water table due to withdrawal of groundwater as from a well.
drill pipe
Definition: Longthe of bollow pine youghy made of steel, used by a drill rig to drill a berebale; also known as drill stem and drill red
Definition: Lengths of hollow pipe usually made of steel, used by a drill rig to drill a borehole; also known as drill stem and drill rod.
drill rod
Definition: See definition for drill rod.

Term
drill stem
Definition: See definiton for drill stem.
drill string
Definition: In horizontal directional drilling, refers to all of the equipment being pushed or pulled into a borehole by the horizontal
directional drill rig (for example, drill pipe, drillhead, back reamer).
drillhead
Definition: The leading end of the drill string; includes the drill bit and a cavity housing the electronic locating equipment (in horizontal
directional drilling).
dual-phase extraction
Acronym: DPE
dynamic viscosity
Definition: A measure of a fluid's resistance to tangential or shear stress.
effective porosity
Definition: The amount of interconnected pore space in a soil or rock through which fluids can pass, expressed as a percent of bulk

Term
volume. Some of the voids and pores in a rock or soil will be filled with static fluid or other material, so that effective porosity is always
less than total porosity.
effluent
Definition: Something that flows out, especially a liquid or gaseous waste stream.
electron acceptor
Definition: A chemical entity that accepts electrons transferred to it from another compound. It is an oxidizing agent that, by virtue of
its accepting electrons, is itself reduced in the process. (see also electron donor and oxidation-reduction.)
electron donor
Definition: A chemical entity that donates electrons to another compound. It is a reducing agent that, by virtue of its donating
electrons, is itself oxidized in the process. (see also electron acceptor and oxidation-reduction)
empirical
Definition: Relying upon or gained from experiment or observation.
enhanced anaerobic oxidative bioremediation
Acronym: EAOB
entrained

Term
Definition: Particulates or vapor transported along with flowing gas or liquid.
enzyme
Definition: (a) Any of numerous proteins or conjugated proteins produced by living organisms and functioning as biochemical
catalysts. (b) a protein that a living organism uses in the process of degrading a specific compound. The protein serves as a catalyst
in the compound's biochemical transformation.
eucaryotes
Definition: An organism having one or more cells with well-defined nuclei.
evaporation
Definition: The process by which a liquid enters the vapor (gas) phase.
ex situ
Definition: Moved from its original place; excavated; removed or recovered from the subsurface.
extraction well
Definition: A well employed to extract fluids (either water, gas, free product, or a combination of these) from the subsurface.
Extraction is usually accomplished by either a pump located within the well or suction created by a vacuum pump at the ground
surface.

Term
facultative
Definition: Used to describe organisms that are able to grow in either the presence or absence of a specific environmental factor (e.g., oxygen). See also facultative anaerobe.
facultative anaerobes
Definition: Microorganisms that can grow in either the presence or the absence of molecular oxygen. In the absence of oxygen these microorganism can utilize another compound (e.g., sulfate or nitrate) as a terminal electron acceptor.
Fick's First Law
Definition: An equation describing the rate at which a gas transfers into solution. The change in concentration of gas in solution is proportional to the product of an overall mass transfer coefficient and the concentration gradient.
Fick's Second Law
Definition: An equation relating the change of concentration with time due to diffusion to the change in concentration gradient with distance from the source of concentration.
field capacity
Definition: The maximum amount of water that a soil can retain after excess water from saturated conditions has been drained by the force of gravity.
flame ionization detector

Term
Acronym: FID
flow tube
Definition: A calibrated flow measuring device made for a specific range of flow velocities and fluids.
flux
Definition: The rate of movement of mass through a unit cross-sectional area per unit time in response to a concentration gradient or
some advective force.
frac-out
Inac-out
Definition: See inadvertent return Preferred Term: inadvertent return
frac tank
Definition: A large steel tank used for storing liquids on-site.
free product
Definition: A petroleum hydrocarbon in the liquid ("free" or non-aqueous) phase. (see also non-aqueous phase liquid, NAPL).
friable
Definition: Easily crumbled, not cohesive or sticky.

Term
fungi
Definition: Aerobic, multicellular, nonphotosynthetic, heterotrophic microorganisms. The fungi include mushrooms, yeast, molds, and
smuts. Most fungi are saprophytes, obtaining their nourishment from dead organic matter. Along with bacteria, fungi are the principal
organisms responsible for the decomposition of carbon in the biosphere. Fungi have two ecological advantages over bacteria: (1)
they can grow in low moisture areas, and (2) they can grow in low pH environments.
gallons per minute
Acronym: gpm
gas chromatograph
Acronym: GC
gate valve
Definition: A valve regulated by the position of a circular plate.
globe valve
Definition: A type of stemmed valve that is used for flow control. The valve has a globe shaped plug that rises or falls vertically when
the stem handwheel is rotated.
gradient

Term
Definition: The rate of change in value of a physical or chemical parameter per unit change in position. For example, hydraulic gradient is equal to the difference in head measured at two points (usually wells) divided by the distance separating the two points. The dimensions of head and distance are both lengths, therefore the gradient is expressed as a dimensionless ratio (L/L).
granular activated carbon
Acronym: GAC
groundwater
Definition: The water contained in the pore spaces of saturated geologic media.
grout
Definition: A watery mixture of cement (and commonly bentonite) without aggregate that is used to seal the annular space around
well casings to prevent infiltration of water or short-circuiting of vapor flow.
gyroscopic steering tool
Definition: Used in horizontal directional drilling, a highly accurate locating technology that uses gyroscopes, accelerometers, and/or
magnetometers to measure the drillhead's position with respect to the Earth's magnetic field and/or an induced magnetic field, and to
measure the drillhead's orientation. All of the information is transmitted to the driller through a wire in the drill pipe; it does not require
any wireless communication or surface access for a receiver. Compare walkover locator and remote magnetic guidance system.
heat capacity

Term
Acronym: HDPE
high-resolution site characterization
Acronym: HRSC
homogeneous
Definition: Uniform in structure or composition at all locations in space.
horizontal directional drilling
Definition: A technology that uses a specialized drill rig and drillhead locating equipment to create a curved borehole along a pre-
determined desired borepath. The drill rig then either pulls or pushes a product, for example well casing, pipeline, telecommunication
cables, sewer pipe into the borehole.
horizontal remediation well
Definition: An environmental remediation well installed using horizontal directional drilling equipment.
hose barb
Definition: A twist-type connector used for connecting a small diameter hose to a valve or faucet
hydraulic conductivity

Term
Definition: A coefficient of proportionality describing the rate at which water can move through a permeable medium. Hydraulic conductivity is a function of both the intrinsic permeability of the porous medium and the kinematic viscosity of the water which flows through it. Also referred to as the coefficient of permeability. Acronym: K
hydraulic gradient
Definition: The change in total potentiometric (or piezometric) head between two points divided by the horizontal distance separating the two points.
hydrocarbon
Definition: Chemical compounds composed only of carbon and hydrogen.
hydrogen peroxide
Definition: Hydrogen peroxide is used to increase the dissolved oxygen content of groundwater to stimulate aerobic biodegradation of organic contaminants. Hydrogen peroxide is infinitely soluble in water, but rapidly dissociates to form a molecule of water and one-half molecule of oxygen. Dissolved oxygen concentrations of greater than 1,000 mg/L are possible using hydrogen peroxide, but high levels of D.O. can be toxic to microorganisms. Acronym: H0
hydrophilic
Definition: Having an affinity for water, or capable of dissolving in water; soluble or miscible in water.
hydrophobic

Term
Definition: Tending not to combine with water, or incapable of dissolving in water; insoluble or immiscible in water. A property
exhibited by non-polar organic compounds, including the petroleum hydrocarbons.
hypoxic
Definition. A condition of low owners concentration, below that considered conching
Definition: A condition of low oxygen concentration, below that considered aerobic.
in-line rotameter
Definition: A flow measurement device for liquids and gases that uses a flow tube and specialized float. The float device is supported
by the flowing fluid in the clear glass or plastic flow tube. The vertical scaled flow tube is calibrated for the desired flow volumes/time.
in situ
Definition: In its original place; unmoved; unexcavated; remaining in the subsurface.
inadvertent return
Definition: An occurrence of drilling fluids escaping from the ground at an unexpected place during horizontal directional drilling; it is
also known as a frac-out.
indigenous
Definition: Living or occurring naturally in a specific area or environment; native.
infiltration

Term
Definition: The downward movement of water through a soil in response to gravity and capillary suction.
infiltration gallery
Definition: An engineered structure that facilitates infiltration of water into the subsurface. Infiltration galleries may consist of one or
more horizontal or vertical perforated pipes, a single gravel-filled trench or a network of such trenches, or a combination of these.
injection well
Definition: A well wood to inight under processo of fluid (liquid or goe) into the subourfees
Definition: A well used to inject under pressure a fluid (liquid or gas) into the subsurface.
inlet well
Definition: A well through which a fluid (liquid or gas) is allowed to enter the subsurface under natural pressure.
inoculate
Definition: To implant microorganisms onto or into a culture medium.
intergranular
Definition: Between the individual grains in a rock or sediment.
intrinsic permeability
Definition: A measure of the relative ease with which a permeable medium can transmit a fluid (liquid or gas). Intrinsic permeability is

Term
a property only of the medium and is independent of the nature of the fluid.
isotropic
Definition: The condition in which hydraulic properties of an aquifer are equal when measured in any direction.
kinematic viscosity
Definition: The ratio of dynamic viscosity to mass density. Kinematic viscosity is a measure of a fluid's resistance to gravity flow: the
lower the kinematic viscosity, the easier and faster the fluid will flow.
knock off technology
Definition: A proprietary method of horizontal directional drilling in which large-diameter drill pipe is used with the well materials
already inside the drill pipe. Once the desired borehole location is reached, the drill bit detaches from the drill pipe, the drill pipe is
withdrawn from the borehole, and the well materials remain in place.
laser-induced fluorescence
Acronym: LIF
leaking underground storage tank
Acronym: LUST

Term
light non-aqueous phase liquid
Acronym: LNAPL
liquid limit
Definition: The lower limit for viscous flow of a soil.
Acronym: LL
liquidity index
Definition: Quantitative value used to assess whether a soil will behave as a brittle solid, semisolid, plastic, or liquid. LI is equal to the
difference between the natural moisture content of the soil and the plastic limit (PL) divided by the plasticity index (PI).
Acronym: LI
lithology
Definition: The gross physical character of a rock or rock types in a stratigraphic section.
low temperature thermal desorption
Acronym: LTTD
lower explosive limit

Term
Definition: The concentration of a gas below which the concentration of vapors is insufficient to support an explosion. LELs for most organics are generally 1 to 5 percent by volume. Acronym: LEL
magnehelic gauge
Definition: A sensitive differential pressure or vacuum gauge manufactured by Dwyer Instrument Co. that uses a precision diaphragm to measure pressure differences. This gauge is manufactured in specific pressure or vacuum ranges such as 0 to 2 inches of water column. Magnehelic gauges are typically used to measure SVE system vacuums.
manifold
Definition: A pipe with several apertures for making multiple connections.
manometer
Definition: An instrument for measuring fluid pressure. Typically a U-shaped tube in which opposing fluid pressures reach an equilibrium. The pressure is equal to the differences in the levels of the fluid on either side of the tube.
mass flux
Definition: The flow rate of contaminant mass through a defined area, usually a portion of a plume cross section; expressed as mass per time per area.
mass spectrometer

Term
Acronym: MS
matrix back-diffusion (rebound)
Definition: Increase in contaminant concentrations after initial treatment has reduced contaminant levels in high permeability zones; caused by low permeability zones releasing contaminants into high permeability zones.
membrane interface probe
Acronym: MIP
mercury, elemental
Acronym: Hg
metabolism
Definition: A term that encompasses all of the diverse reactions by which a cell processes food material to obtain energy and the compounds from which new cell components are made.
methanogenic
Definition: Referring to the formation of methane by certain anaerobic bacteria during the process of anaerobic fermentation. methyl tertiary-butyl ether

Term
Definition: A fuel oxygenate. It and other fuel additives (such as tertiary butyl alcohol (TBA), ethanol, and methanol) are highly soluble in water and highly mobile in the subsurface. Acronym: MTBE
microaerophilic
Definition: Obligate aerobes that function best under conditions of low oxygen concentration.
microcosm
Definition: A diminutive, representative system analogous to a larger system in composition, development, or configuration. As used
in biodegradation treatability studies, microcosms are typically constructed in glass bottles or jars.
microorganisms
Definition: Microscopic organisms including bacteria, protozoans, yeast, fungi, mold, viruses, and algae.
milligrams per liter
Acronym: mg/L
mineralization
Definition: The release of inorganic chemicals from organic matter in the process of aerobic or anaerobic decay.

Term
moisture content
Definition: The amount of water lost from a soil upon drying to a constant weight, expressed as the weight per unit weight of dry soil
or as the volume of water per unit bulk volume of the soil. For a fully saturated medium, moisture content equals the porosity.
molecular diffusion
Definition: Process whereby molecules of various gases tend to intermingle and eventually become uniformly dispersed.
molecular weight
Definition: The amount of mass in one mole of molecules of a substance as determined by summing the masses of the individual
atoms which make up the molecule.
monoaromatic
Definition: Aromatic hydrocarbons containing a single benzene ring.
mud motor
Definition: A horizontal directional drilling tool that causes the drill bit to rotate while the drill pipe does not rotate; it is attached as part
of the drill string, between the drillhead and the drill pipe.
national pollutant discharge elimination system

Term
Acronym: NPDES
non-aqueous phase liquid
Definition: Contaminants that remain as the original bulk liquid in the subsurface. (see also free product) Acronym: NAPL
nutrients
Definition: Major elements (e.g., nitrogen and phosphorus) and trace elements (including sulfur, potassium, calcium, and magnesium) that are essential for the growth of organisms.
obligate aerobes
Definition: Organisms that require the presence of molecular oxygen (0) for their metabolism.
obligate anaerobes
Definition: Organisms for which the presence of molecular oxygen is toxic. These organisms derive the oxygen needed for cell synthesis from chemical compounds.
occlude
Definition: To cause to become obstructed or closed and thus prevent passage either into or from.
octanol/water partition coefficient

Term
Definition: A coefficient representing the ratio of the solubility of a compound in octanol (a non-polar solvent) to its solubility in water (a polar solvent). The higher the Kow, the more non-polar the compound. Log Kow is generally used as a relative indicator of the tendency of an organic compound to adsorb to soil. Log Kow values are generally inversely related to aqueous solubility and directly proportional to molecular weight. Acronym: Kow
off-gas treatment system
Definition: Refers to the unit operations used to treat (i.e. condense, collect, or destroy) contaminants in the purge gas from the thermal desorber.
Office of Underground Storage Tanks (USEPA, Washington, DC)
Acronym: OUST
olefins
operation and maintenance
Acronym: O&M
orifice plate
Definition: A flow measurement device for liquids or gases that uses a restrictive orifice plate consisting of a machined hole that

Term
produces a jet effect. Typically the orifice meter consists of a thin plate with a square edged, concentric, and circular orifice. The pressure drop of the jet effect across the orifice is proportional to the flow rate. The pressure drop can be measured with a manometer or differential pressure gauge.
oxidation-reduction (redox)
Definition: A chemical reaction consisting of an oxidation reaction in which a substance loses or donates electrons, and a reduction reaction in which a substance gains or accepts electrons. Redox reactions are always coupled because free electrons cannot exist in solution and electrons must be conserved.
oxidation-reduction (redox) potential
Definition: A measure of an aqueous solution's tendency to either release or accept electrons. Oxidizing systems tend to accept electrons; reducing systems tend to release electrons. paraffins
Definition: See definition for alkanes.
partial pressure
Definition: The portion of total vapor pressure in a system due to one or more constituents in the vapor mixture. parts per billion
Acronym: ppb

Term
parts per million
Acronym: ppm
permeability
Definition: A qualitative description of the relative ease with which rock, soil, or sediment will transmit a fluid (liquid or gas). Often
used as a synonym for hydraulic conductivity or coefficient of permeability.
permeable reactive barrier
Acronym: PRB
рН
Definition: A measure of the acidity of a solution. pH is equal to the negative logarithm of the concentration of hydrogen ions in a
solution. A pH of 7 is neutral. Values less than 7 are acidic, and values greater than 7 are basic.
photoionization detector
Acronym: PID
phototrophs

Term
Definition: Organisms that use light to generate energy (by photosynthesis) for cellular activity, growth, and reproduction.
pilot test
Definition: Operation of a small-scale version of a larger system to gain information relating to the anticipated performance of the
larger system. Pilot test results are typically used to design and optimize the larger system.
pitot tube
Definition: a device used to measure the total pressure of a fluid stream that is essentially a tube attached to a manometer at one end
and pointed upstream at the other.
plastic limit
Definition: The lower limit of the plastic state of a soil.
Acronym: PL
plastic soil
Definition: One that will deform without shearing (typically silts or clays). Plasticity characteristics are measured using a set of
parameters known as Atterberg Limits.
plasticity index
Definition: The range of water content in which soil is in a plastic state. PI is calculated as the difference between the percent liquid
limit and percent plastic limit.
Acronym: PI

Term
polyaromatic hydrocarbon
Definition: Aromatic hydrocarbons containing more than one fused benzene ring. Polyaromatic hydrocarbons are commonly designated PAH.
Acronym: PAH, PNA
polynuclear aromatic hydrocarbon
Definition: synonymous with polyaromatic hydrocarbon. Designated PNA.
Acronym: PNA
polyvinyl chloride
Acronym: PVC
pore volume
Definition: (1) the total volume of pore space in a given volume of rock or sediment. Pore volume usually relates to the volume of air or water that must be moved through contaminated material in order to flush the contaminants. (2) the volume of water (or air) that will completely fill all of the void space in a given volume of porous matrix. Pore volume is equivalent to the total porosity. The rate of decrease in the concentration of contaminants in a given volume of contaminated porous media is directly proportional to the number of pore volumes that can be exchanged (circulated) through the same given volume of porous media.
porosity, effective

Term
Definition: A measure of the connected aquifer void space within the aquifer. Effective porosity is lower than total porosity in most geological settings.
porosity, total
Definition: The volume fraction of a rock or unconsolidated sediment not occupied by solid material but usually occupied by water and/or air. Primary porosity is the percentage of the voids in the rock at the time of formation, and secondary porosity refers to the void space from fractures and dissolution.
pounds per square inch
Definition: A unit of pressure or pressure drop across a flow resistance. One psi is equivalent to the pressure exerted by 2.31 feet of water column. Acronym: psi
pounds per square inch (gauge)
Definition: 0 psig = 14.696 psia (psi absolute) = 1.0 atmosphere. Acronym: psig
pressure gradient
Definition: A pressure differential in a given medium(e.g., water or air) which tends to induce movement from areas of higher pressure to areas of lower pressure.
procaryote

Term
Definition: A cellular organism in which the nucleus has no limiting membrane.
protozoa
Definition: Single-celled, eucaryotic microorganisms without cell walls. Most protozoa are free-living although many are parasitic. The
majority of protozoa are aerobic or facultatively anaerobic heterotrophs.
pugmill
Definition: A chamber in which water and soil are mixed together. Typically mixing is aided by an internal mechanical
stirring/kneading device.
pullback
Definition: In horizontal directional drilling, the stage of drilling a surface-to-surface well in which the well materials are pulled into the borehole.
quality assurance
Acronym: QA
quality control
Acronym: QC

Term
radius of influence
Definition: The maximum distance away from an air injection or extraction source that is significantly affected by a change in pressure and induced movement of air. Acronym: ROI
reagent
Definition: A substance or solution used in a chemical reaction, especially those used in laboratory work to detect, measure, or produce other substances.
recalcitrant
Definition: Unreactive, nondegradable; refractory. recirculation system
Definition: A type of in-situ bioremediation system designed to increase the hydraulic gradient and accelerate the distribution of amendments across the contaminated area. Recirculation systems typically have extraction wells drawing groundwater from downgradient locations and injection wells injecting water with amendments into the source area. redox
Preferred Term: oxidation-reduction (redox)
refractory index

Term
Definition: A measure of the ability of a substance to be biodegraded by bacterial activity. The lower the refractory index, the greater the biodegradability.
remote magnetic guidance system
Definition: In horizontal directional drilling, a locating technology that uses a sensor in the sonde that senses its location and
orientation relative to a natural or induced magnetic field. The sensor sends the drillhead's orientation information to the driller
through a wire within the drill pipe; the wire also supplies power to the sonde. Compare to gyroscopic steering tool and walkover locator.
retardation
Definition: Preferential retention of contaminant movement in the subsurface resulting from adsorptive processes or solubility
differences.
saturated zone
Definition: The zone in which all the voids in the rock or soil are filled with water at greater than atmospheric pressure. The water
table is the top of the saturated zone in an unconfined aquifer.
sentinel well
Definition: A groundwater monitoring well situated between a sensitive receptor downgradient and the source of a contaminant plume
upgradient. Contamination should be first detected in the sentinel well which serves as a warning that contamination may be moving
closer to the receptor. The sentinel well should be located far enough upgradient of the receptor to allow enough time before the
contamination arrives at the receptor to initiate other measures to prevent contamination from reaching the receptor, or in the case of

_
Term
a supply well, provide for an alternative water source.
septa fitting
Definition: A special fitting used to seal vials (a liner for a threaded cap) or gas chromatographs (GCs) to provide closure. Septas can
be manufactured in single, double, or triple layers of silicone rubber and other plastic materials. A syringe with a measured quantity of
contaminant can be injected through a septa closure and into a GC column for separation analysis.
sequester
Definition: To undergo sequestration.
sequestration
Definition: The inhibition or stoppage of normal ion behavior by combination with added materials, especially the prevention of
metallic ion precipitation from solution by formation of a coordination complex with a phosphate.
SESOIL
Definition: A one-dimensional model for estimating pollutant distribution in an unsaturated soil column. SESOIL results are commonly
used to estimate the source term for groundwater transport modeling of the saturated zone.
short circuiting
Definition: The entry of ambient air into an extraction well (used for SVE and bioventing) without first passing through the
contaminated zone. Short circuiting may occur through utility trenches, incoherent well or surface seals, or layers of high permeability
geologic materials.

Term
soil moisture
Definition: The water contained in the pore spaces in the unsaturated zone.
soil organic carbon partition coefficient
Definition: A constant that describes a compound's equilibrium condition between organic carbon and the contaminant concentrations in an aqueous solution. Higher Koc values indicate more contaminant mass is likely to be retained in soil and therefore less readily bioavailable.
Acronym: Koc
soil vapor extraction Definition: An environmental cleanup method that induces a vacuum within unsaturated soil to extract contaminated vapors from the ground and collect them for treatment. Acronym: SVE
solubility
Definition: The amount of mass of a compound that will dissolve in a unit volume of solution.
sonde
Definition: Used in horizontal directional drilling, a locating device in the drillhead that transmits wireless radio signals to a receiver on
the surface. These signals inform the driller about the drillhead's location, depth, and orientation.
sorbent canisters

T
Term
Definition: Gas-tight canisters typically filled with activated carbon (charcoal) for collection and transport of vapor samples. In the
laboratory the vapors are desorbed and analyzed to identify the organic compounds and quantify their concentration.
sorbent tubes
Definition: Glass tubes filled with a sorbent material that reacts chemically with specific organic compounds. Based on the nature of
the sorbent and the extent of the chemical reaction, organic compounds can be identified and their concentration quantified.
sorption
Definition: A general term used to encompass the processes of absorption, adsorption, ion exchange, and chemisorption.
sparge
Definition: Injection of air below the water table to strip dissolved volatile organic compounds and/or oxygenate the groundwater to
facilitate aerobic biodegradation of organic compounds.
specific gravity
Definition: The dimensionless ratio of the density of a substance with respect to the density of water. The specific gravity of water is
equal to 1.0 by definition. Most petroleum products have a specific gravity less than 1.0, generally between 0.6 and 0.9. As such, they
will float on waterthese are also referred to as LNAPLs, or light non-aqueous phase liquids. Substances with a specific gravity
greater than 1.0 will sink through waterthese are referred to as DNAPLs, or dense non-aqueous phase liquids.
sticky limit

Term
Definition: The limit at which a soil loses its ability to adhere to a metal blade.
stratification
Definition: Layering or bedding of geologic materials (e.g., rock or sediments).
stratum
Definition: A horizontal layer of geologic material of similar composition, especially one of several parallel layers arranged one on top
of another.
sump
Definition: A pit or depression where liquids drain, collect, or are stored.
surface-to-surface well
Definition: A well drilled using horizontal directional drilling with an exit hole, through which the well materials are pulled into the
borehole. Compare to blind well.
Tedlar bags
Definition: Gas-tight bags constructed of non-reactive material (Tedlar) for the collection and transport of gas/vapor samples.
terminal electron acceptor
Definition: A compound or molecule that accepts an electron (is reduced) during metabolism (oxidation) of a carbon source. Under

Term
aerobic conditions molecular oxygen is the terminal electron acceptor. Under anaerobic conditions a variety of terminal electron acceptors may be used. In order of decreasing redox potential, these TEAs include nitrate, manganic manganese, ferric iron, sulfate, and carbon dioxide. Microorganisms preferentially utilize electron acceptors that provide the maximum free energy during respiration. Of the common terminal electron acceptors listed above, oxygen has the highest redox potential and provides the most free energy during electron transfer. Acronym: TEA
tertiary butyl alcohol
Acronym: TBA
thermal desorber
Definition: Describes the primary treatment unit that heats petroleum-contaminated materials and desorbs the organic materials into a purge gas or off-gas.
thermal desorption system
Definition: Refers to a thermal desorber and associated systems for handling materials and treated soils and treating offgases and residuals.
thrust/pullback capacity
Definition: A measure (in pounds) of how much force a horizontal directional drill rig is able to apply when pushing or pulling the drill string; it is used to rate the size of a drill rig.

Term
total dissolved solids
Acronym: TDS
total petroleum hydrocarbons
Definition: A measure of the concentration or mass of petroleum hydrocarbon constituents present in a given amount of air, soil, or water. The term total is a misnomer, in that few, if any, of the procedures for quantifying hydrocarbons are capable of measuring all fractions of petroleum hydrocarbons present in the sample. Volatile hydrocarbons are usually lost in the process and not quantified. Additionally, some non-petroleum hydrocarbons may be included in the analysis. Acronym: TPH
total recoverable petroleum hydrocarbons
Definition: an EPA method (418.1) for measuring total petroleum hydrocarbons in samples of soil or water. Hydrocarbons are extracted from the sample using a chlorofluorocarbon solvent (typically Freon-113) and quantified by infrared spectrophotometry. The method specifies that the extract be passed through silica gel to remove the non-petroleum fraction of the hydrocarbons. Acronym: TRPH
toxicity characteristic leaching procedure (EPA Method 1311)
Acronym: TCLP
travel time

Term
Definition: The time it takes a contaminant to travel from the source to a particular point downgradient.
tripolyphosphates
Definition: Salts with P3O10-5 anion. Most common is sodium tripolyphosphate [Na5P3O10].
turbine wheel
Definition: A rotor designed to convert fluid energy into rotational energy. Hydraulic turbines are used to extract energy from water as
the water velocity increases due to a change in head or kinetic energy at the expense of the potential energy as the water flows from
a higher elevation to a lower elevation. The fluid velocity tangential component contributes to the rotation of the rotor in a
turbomachine.
unconfined aquifer
Definition: An aquifer in which there are no confining beds between the capillary fringe and land surface, and where the top of the
saturated zone (the water table) is at atmospheric pressure.
underground storage tank
Acronym: UST
unsaturated

Term
Definition: The characteristic of a carbon atom in a hydrocarbon molecule that shares a double bond with another carbon atom.
unsaturated zone
Definition: The zone between land surface and the capillary fringe within which the moisture content is less than saturation and pressure is less than atmospheric. Soil pore spaces also typically contain air or other gases. The capillary fringe is not included in the unsaturated zone.
upgradient
Definition: In the direction of increasing potentiometric (piezometric) head.
upper explosive limit
Acronym: UEL
vacuum draft tube
Definition: A narrow tube lowered into an extraction well through which a strong vacuum is pulled via a suction pump at ground
surface. Fluids (gas, water, and/or free product) are drawn into the draft tube and conveyed to the surface for treatment or disposal.
Depending upon the configuration of the extraction system, the inlet of the draft tube may be either above or below the static level of
the liquid in the well.
vadose zone
Definition: The zone between land surface and the water table within which the moisture content is less than saturation (except in the

Term
capillary fringe) and pressure is less than atmospheric. Soil pore spaces also typically contain air or other gases. The capillary fringe is included in the vadose zone.
vapor density
Definition: The amount of mass of a vapor per unit volume of the vapor.
vapor pressure
Definition: The force per unit area exerted by a vapor in an equilibrium state with its pure solid, liquid, or solution at a given
temperature. Vapor pressure is a measure of a substance's propensity to evaporate. Vapor pressure increases exponentially with an
increase in temperature.
venturi
Definition: A short tube with a constricted throat for determining fluid pressures and velocities by measuring differential pressures
generated at the throat as a fluid traverses the tube.
viscosity
Definition: A managura of the internal friction of a fluid that provides registered to shear within the fluid. The greater the foress of
Definition: A measure of the internal friction of a fluid that provides resistance to shear within the fluid. The greater the forces of internal friction (i.e. the greater the viscosity), the less easily the fluid will flow.
volatile organic compound
Acronym: VOC

Term
volatilization
Definition: The process of transfer of a chemical from the aqueous or liquid phase to the gas phase. Solubility, molecular weight, and
vapor pressure of the liquid and the nature of the gas-liquid interface affect the rate of volatilization.
walkover locator
Definition: Used in horizontal directional drilling, a commonly-used locating technology in which a battery-operated transmitter, called
a sonde, in the drill-head uses wireless signals to send information about the drillhead's location, depth, and orientation to a handheld
receiver carried by a crew member on the surface. These signals allow the driller to adjust the drilling process to keep the drillhead on
the desired borepath. Compare to gyroscopic steering tool and remote magnetic guidance system.
water table
Definition: The water surface in an unconfined aquifer at which the fluid pressure in the pore spaces is at atmospheric pressure.
weathering
weathering
Definition: The process during which a complex compound is reduced to its simpler component parts, transported via physical
processes, or biodegraded over time.
wellhead
Definition: The area immediately surrounding the top of a well, or the top of the well casing.
windrow

Term

Definition: A low, elongated row of material left uncovered to dry. Windrows are typically arranged in parallel.

wire-line system

Definition: See definition for remote magnetic guidance system.